

# Ei261ENRC - Carbon Monoxide Alarm

**MAINS POWERED 230V~**  
**Rechargeable Battery Back-Up**

## Key Features

- ▶ Proven electrochemical 10 year CO sensor
- ▶ AudioLINK data download
- ▶ Hardwire interconnect
- ▶ Tamper-proof rechargeable Lithium battery back-up
- ▶ Pre alarm indication gives early warning of CO
- ▶ Easy-fit base
- ▶ Audible and visual "End of life" indication
- ▶ Easy to use Test/Hush button
- ▶ Memory feature
- ▶ Integrated piezoelectric sounder
- ▶ 5 Year guarantee

## Product Description

The Ei261ENRC Carbon Monoxide Alarm is fitted with a high performance, proven 10 year electrochemical sensor to detect the presence of toxic levels of Carbon Monoxide (CO). Each sensor is individually calibrated and tested in Carbon Monoxide gas to ensure accuracy. It is powered by 230V AC with a rechargeable 10 year built in battery backup supply to ensure continuous operation (up to 4 weeks) in the event of a power failure.

The Alarm is supplied with the "Easi-fit" base to facilitate quick and simple installation, combined with easy detector head removal and replacement. The Easi-fit base automatically connects both mains power and battery as the detector head slides on.

When the Alarm detects potentially dangerous levels of CO, the red LED flashes and if the CO persists the alarm will sound. The rate of flashing of the red LED indicates the level of CO. The higher the level of CO detected, the sooner the alarm will sound.

The AudioLINK feature facilitates acoustic download of the Alarm parameters and status using the Ei Electronics AudioLINK app.

The Ei261ENRC may operate as a standalone Alarm or may be interconnected via hardwire to communicate with compatible Ei Electronics Alarms and accessories. Up to 12 devices can be interconnected.

The Alarm self-checks its sensor, battery voltage and internal circuitry regularly. Any fault condition will be indicated by a combination of visual and/or audible indicators.

The memory feature allows an Alarm that has previously activated to be easily identified (as the red LED will continue to flash for 24hrs after the event or afterwards when you press the Test button).

The Test/Silence button allows the user to check the operation of the Alarm. This will check the sounder, battery voltage, sensor and internal circuitry.



## Technical Specification

<b>Sensor Type:</b>	Electrochemical
<b>Product life:</b>	10 years
<b>Supply Voltage:</b>	230V AC, 50 Hz
<b>Battery back-up:</b>	Rechargeable Lithium battery backup
<b>Sound Level:</b>	85 dB(A) at 3m
<b>Button Test:</b>	Checks the sensor, electronics and horn
<b>Silence function:</b>	Silences alarm once for 4 minutes if <150ppm
<b>Data download:</b>	Via the AudioLINK app
<b>Visual indicators:</b>	<b>Green LED</b> - Power
	<b>Red LED</b> - Pre-alarm, alarm, hush mode and memory
	<b>Yellow LED</b> - Fault
<b>Memory Feature:</b>	Records last alarm event
<b>End of Life:</b>	Audible and visual indicators (3 beeps with 3 yellow flashes every 40 seconds)
<b>Normal Operating and Storage Temperature Range:</b>	-10°C to 40°C <sup>1</sup>
<b>Normal Operating and Storage Humidity Range:</b>	15 % to 95 % Relative Humidity (non-condensing)
<b>Plastic material:</b>	UL94V0 flame retardant
<b>Fixing:</b>	Screw fixings and mounting plate supplied
<b>Dimensions:</b>	Product - 155mm x 128mm x 48mm Packaged - 160mm x 130mm x 50mm
<b>Weight:</b>	305g (Pack +45g)
<b>Warranty:</b>	5 year (limited) warranty
<b>Approvals:</b>	



KM 86596  
 EN 50291-1:2010 + A1:2012

Manufactured to ISO 9001 quality standards  
 Specifications are subject to change

1. Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.

Shannon Free Zone, Shannon, Co. Clare, Ireland  
 Tel: +353 61 471277 Fax: +353 61 471053  
 email: sales@eielectronics.ie  
 web: www.eielectronics.com