

# Ei650C - Optical Smoke Alarm

**Hard wire Interconnection**  
**10 Year Lithium battery**

## Key Features

- ▶ High performance optical sensor
- ▶ Hardwire interconnect
- ▶ Wireless interconnect when fitted with Ei600MRF **RadioLINK+** module
- ▶ Easy install twist-on base
- ▶ Easy to use large Test/Hush button
- ▶ Alarm ramp up in Test mode
- ▶ Built in sounder - 85dB(A) at 3 metres
- ▶ 5 Year guarantee

## Product Description

The Ei650C optical Smoke Alarm is fitted with a proprietary photoelectric sensor to quickly sense low energy smoke particles. This optical Alarm is sensitive to all domestic fire types but is especially sensitive to smoldering fires.

In standby, there are no visible or audible indicators on the Ei650 range that could disturb the occupant making it ideal for bedrooms and children's rooms.

It is powered by a sealed 10 year Lithium battery that will last the entire product life in normal conditions of use.

The Ei650C may operate as a standalone or may be interconnected via hardwire or wirelessly using the Ei600MRF RadioLINK+ module (sold separately) to communicate with compatible Ei Electronics Alarms and accessories. Up to 12 devices can be interconnected.

The Ei650C is fitted with a large easy to use Test Button to facilitate frequent testing of the Alarm. For better hearing comfort, the sound level of the alarm increases progressively in Test mode. The Test button can also be used to silence nuisance alarms, e.g. cooking fumes, for a 10 minute period.

The Ei650C self-checks its chamber sensor, battery voltage and internal circuitry every 40 seconds. Any fault condition found will be indicated by a combination of Red LED flashes and/or sound beeps.


The Ei650 range features a high performance optical chamber protected by a sealed mesh screen to reduce insect and dust contamination and EMC protection to reduce false alarms.

The Alarm has a twist on mounting base which has multiple fixing points so it can be easily installed. The alarm is not powered until it is twisted onto the mounting base, thus avoiding battery power consumption during storage and prior to installation.



## Technical Specification

<b>Sensor Type:</b>	Photoelectric
<b>Product life:</b>	10 years
<b>Supply Voltage:</b>	3V Lithium Battery (non replaceable)
<b>Sound Level:</b>	85 dB(A) at 3m (except in Test mode)
<b>Button Test:</b>	Checks sensor, electronics, battery and horn
<b>Silence function:</b>	Silences alarm for 10 minutes
<b>Visual Indicators:</b>	Red LED: on power up, alarm, hush mode & fault
<b>Insect screen:</b>	Fine Mesh
<b>Fixings:</b>	Screw fixings and mounting plate supplied
<b>Normal Operating and Storage Temperature Range:</b>	-10°C to 40°C <sup>1</sup>
<b>Normal Operating and Storage Humidity Range</b>	15 % to 95 % Relative Humidity (non-condensing)
<b>Dimensions:</b>	Product - 115mm x 50mm Package - 150mm x 120mm x 56mm
<b>Weight:</b>	185g (pack +50g)
<b>Warranty:</b>	5 year (limited) warranty
<b>Approvals:</b>	



Manufactured to ISO 9001 quality standards  
 Specifications are subject to change

1. Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.