

Ei650W - Optical Smoke Alarm

Optional Wireless Interconnect 10 Year Lithium battery

Key Features

- ▶ High performance optical sensor
- ▶ Wireless interconnect when fitted with Ei600MRF RadioLINK+ module
- ▶ Easy install twist-on base
- ▶ Easy to use large Test/Hush button
- ▶ Alarm ramp up in Test mode
- ▶ Built in sounder - 85dB(A) at 3 metres
- ▶ 5 Year guarantee

Product Description

The Ei650W optical Smoke Alarm is fitted with a proprietary photoelectric sensor to quickly sense low energy smoke particles. This optical Alarm is sensitive to all domestic fire types but is especially sensitive to smoldering fires.

In standby, there are no visible or audible indicators on the Ei650 range that could disturb the occupant making it ideal for bedrooms and children's rooms.

It is powered by a sealed 10 year Lithium battery that will last the entire product life in normal conditions of use.

The Ei650W may operate as a standalone or may be interconnected wirelessly using the Ei600MRF RadioLINK+ module (sold separately) to communicate with compatible Ei Electronics Alarms and accessories. Up to 12 RF devices can be interconnected.

The Ei650W is fitted with a large easy to use Test Button to facilitate frequent testing of the Alarm. For better hearing comfort, the sound level of the alarm increases progressively in Test mode. The Test button can also be used to silence nuisance alarms, e.g. cooking fumes, for a 10 minute period.

The Ei650W self-checks its chamber sensor, battery voltage and internal circuitry every 40 seconds. Any fault condition found will be indicated by a combination of Red LED flashes and/or sound beeps.


The Ei650 range features a high performance optical chamber protected by a sealed mesh screen to reduce insect and dust contamination and EMC protection to reduce false alarms.

The Alarm has a twist on mounting base which has multiple fixing points so it can be easily installed. The alarm is not powered until it is twisted onto the mounting base, thus avoiding battery power consumption during storage and prior to installation.



Technical Specification

Sensor Type:	Photoelectric
Product life:	10 years
Supply Voltage:	3V Lithium Battery (non replaceable)
Sound Level:	85 dB(A) at 3m (except in Test mode)
Button Test:	Checks sensor, electronics, battery and horn
Silence function:	Silences alarm for 10 minutes
Visual Indicators:	Red LED: on power up, alarm, hush mode & fault
Insect screen:	Fine Mesh
Fixings:	Screw fixings and mounting plate supplied
Normal Operating and Storage Temperature Range:	-10°C to 40°C ¹
Normal Operating and Storage Humidity Range	15 % to 95 % Relative Humidity (non-condensing)
Dimensions:	Product - 115mm x 50mm Package - 150mm x 120mm x 56mm
Weight:	185g (pack +50g)
Warranty:	5 year (limited) warranty
Approvals:	



Manufactured to ISO 9001 quality standards
Specifications are subject to change

1. Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.