

# Ei650i - Intelligent Optical Smoke Alarm

**Stand Alone**  
**10 Year Lithium battery**

## Key Features

- ▶ High performance optical sensor
- ▶ Automatic dust compensation
- ▶ AudioLINK data download
- ▶ Fault hush and Diagnostics features
- ▶ Easy install twist-on base
- ▶ Large easy to use Test/Hush Button
- ▶ Alarm ramp up in Test mode
- ▶ Built in sounder - 85dB(A) at 3 metres
- ▶ Specific Fault Led
- ▶ Records previous alarm activation
- ▶ 5 Year guarantee

## Product Description

The Ei650i optical Smoke Alarm is fitted with a proprietary photoelectric sensor to quickly sense low energy smoke particles. This optical Alarm is sensitive to all domestic fire types but is especially sensitive to smoldering fires.

The Ei650 range features a high performance optical chamber protected by a sealed mesh screen to reduce insect and dust contamination and EMC protection to reduce false alarms. In addition the Ei650i has an automatic **dust compensation** feature reducing further the risk of false alarms caused by dust build up.

The AudioLINK feature facilitates acoustic download of the Alarm parameters and status using the Ei Electronics AudioLINK app.

The Ei650i is fitted with a large easy to use Test Button to facilitate frequent testing of the Alarm. For better hearing comfort for professionals who regularly test these products and the occupant, the sound level of the alarm increases progressively in Test mode. The Test button can also be used to silence nuisance alarms (e.g. cooking fumes) for a 10 minute period and fault beeps for 12 hours (low battery and sensor fault).

The Ei650i self-checks its chamber sensor, battery voltage and internal circuitry every 40 seconds. Any fault condition found will be indicated by a combination of Yellow LED flashes and sound beeps.

The Ei650i is designed with advanced diagnostics to help pre-warn of possible impending fault conditions.

The Alarm has a twist on mounting base which has multiple fixing points so it can be easily installed. The alarm is not powered until it is twisted onto the mounting base, thus avoiding battery power consumption during storage and prior to installation.



## Technical Specification

<b>Sensor Type:</b>	Photoelectric
<b>Product life:</b>	10 years
<b>Supply Voltage:</b>	3V Lithium Battery (non replaceable)
<b>Sound Level:</b>	85 dB(A) at 3m
<b>Button Test:</b>	Checks sensor, electronics, battery and horn
<b>Silence function:</b>	Silences alarm for 10 minutes Silences fault beeps for 12hrs
<b>Data download:</b>	Via the AudioLINK app
<b>Adv. diagnostic:</b>	Included
<b>Visual Indicators:</b>	<b>Red LED:</b> on power up, alarm, hush mode and memory <b>Yellow LED:</b> on power up and fault
<b>Memory Feature:</b>	Records last alarm event
<b>Insect screen:</b>	Fine Mesh
<b>Fixings:</b>	Screw fixings and mounting plate supplied
<b>Normal Operating and Storage Temperature Range:</b>	-10°C to 40°C <sup>1</sup>
<b>Normal Operating and Storage Humidity Range</b>	15 % to 95 % Relative Humidity (non-condensing)
<b>Plastic material:</b>	UL94HB
<b>Dimensions:</b>	Product - 115mm x 50mm Package - 150mm x 120mm x 56mm
<b>Weight:</b>	185g (pack +50g)
<b>Warranty:</b>	5 year (limited) warranty
<b>Approvals:</b>	



0786-CPR-21052  
 DOP 13-0002  
 EN 14604:2005



G211009

Manufactured to ISO 9001 quality standards  
 Specifications are subject to change

1. Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.

Shannon Free Zone, Shannon, Co. Clare, Ireland  
 Tel: +353 61 471277 Fax: +353 61 471053  
 email: sales@eielectronics.ie  
 web: www.eielectronics.com